

# SHORT FORM

\*\*\*\*\*

Please indicate the following letters specification, we would provide and quote to our best service, to meet your kind prompt inquires.

## A. MATERIAL:

- a. steel: a. C-1022AK b. C-1018AK c. 1006A/8A-CHQ d. others  
b. stainless steel: a.(A2) AISI 302HQ c.(A2) AISI 304M e. AISI 410  
b.(A2) AISI 305J1 d.(A4) AISI 316C f. AISI 430  
c. solid brass  
d. aluminum  
e. nylon plastic

## B. SCREWS:

- a. self-tapping c. chipboard e. particle board g. drywall i. special  
b. self-drilling d. wood f. sheet metal h. machine

C. STANDARD DIAMETER : 1.60 - 10.00 mm ( 1/8 " - 3/8 " inch )

D. STANDARD LENGTH : 5.00 - 400.00 mm ( 3/16 " - 16 " inch )

## E. HEAD TYPE:

- a. pan c. oval e. truss g. cheese i. double-flat k. fillister  
g. flat d. round f. button h. hex j. hex-washer l. others

## F. THREAD FORMING:

- a. type A d. type D (1) g. type G j. type 17 m. TWIN-FAST  
b. type AB (B) e. type 23 (T) h. type BF K. TAPTITE n. COARSE  
c. type 25 (BT) f. type U i. type F l. HI-LO o. others

## G. RECESS:

- a. pozi-druve d. phillips e. one way f. saw slotted h. others  
b. 6 - lobes ( Torx from T-10 to T-40 ... ) g. struck slot  
c. combinations ( pozi w/slot, square w/slot, phillips w/slot ... )

## H. FINISH:

- a. plain d. phosphated g. brass j. black-finish  
b. zinc e. chrome h. bronze k. black-oxidized  
c. yellow-zinc f. nickel i. antique-brass l. black-zinc  
m. hot-dip galvanized zinc o. dacrotized 320 q. kylan coating  
n. machanical galvanized p. ruspert r. coating long  
s. special thickness treatment t. wax coated u. others

## I. HEAT-TREATMENT:

- a. hardened b. unhardened c. bright hardened

## J. HEAD PAINTED:

- a. powder & colour b. liquid & colour c. others

## K. PLASTIC COVER:

- a. truss type ( brown ) for outside dia.: 1) 2.40 mm 2) 2.90 mm.  
b. cover type ( white ) for outside dia.: 1) 3.80 mm 2) 4.00 mm.

A	B	C	—	D	E	F	—	G	H	I	—	J	K	L
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

TENGSCREW CO., LTD.  
MR. JOHNSON TENG  
MARKETING MANAGER

OUT

NOV 03 1999