

# HIGH QUALITY FASTENERS

If you are sourcing overseas' high quality fasteners, let us put our assets to work for you to compliment your manufacturing and marketing programs. Please do not hesitate to send your enquires.

## MAIN PRODUCT:

SELF-TAPPING SCREWS  
CHIPBOARD SCREWS  
DRYWALL SCREWS  
PARTICLE BOARD SCREWS  
SELF-DRILLING SCREWS  
NYLON PLASTIC SCREWS  
SPECIAL SCREWS

## MATERIAL:

STEEL: CARBON STEEL 1008/1018/1022  
STAINLESS STEEL: 302HQ/304M/305/316/T410/430  
BRASS  
NYLON PLASTIC



TENGSCREW

NO. 106 MA-SU RD., WAN-LI DISTRICT,  
NEW-TAIPEI-CITY, TAIWAN, R. O. C.  
TELEPHONE : 8862 - 2492 - 7747  
FACSIMILES : 8862 - 2492 - 2696  
P.O.BOX:58 NEW -TAIPEI-CITY, TAIWAN, ROC  
EMAIL:TENSCREW@MS34.HINET.NET

a) NUTS / A2 ( SUS 304 S.S. ) INSERT SLOT BY LATHE  
b) SCREWS DRILL HOLES & SAW SLOT BY DRILLING & CUTTING



c) DRILL HOLE IN THE SOCKET RECESS BY A2-70 STAINLESS STEEL

Special Fastener For Head Model & Recess Type



Special Fastener For Recess Type & thread Forming



# SHORT FORM

\*\*\*\*\*

Please indicate the following letters specification, we would provide and quote to our best service, to meet your kind prompt inquires.

## A. MATERIAL:

- a. steel: a. C-1022AK b. C-1018AK c. 1006A/8A-CHQ d. others  
b. stainless steel: a.(A2) AISI 302HQ c.(A2) AISI 304M e. AISI 410  
b.(A2) AISI 305J1 d.(A4) AISI 316C f. AISI 430  
c. solid brass  
d. aluminum  
e. nylon plastic

## B. SCREWS:

- a. self-tapping c. chipboard e. particle board g. drywall i. special  
b. self-drilling d. wood f. sheet metal h. machine

C. STANDARD DIAMETER : 1.60 - 10.00 mm ( 1/8 " - 3/8 " inch )

D. STANDARD LENGTH : 5.00 - 400.00 mm ( 3/16 " - 16 " inch )

## E. HEAD TYPE:

- a. pan c. oval e. truss g. cheese i. double-flat k. fillister  
g. flat d. round f. button h. hex j. hex-washer l. others

## F. THREAD FORMING:

- a. type A d. type D (1) g. type G j. type 17 m. TWIN-FAST  
b. type AB (B) e. type 23 (T) h. type BF K. TAPTITE n. COARSE  
c. type 25 (BT) f. type U i. type F l. HI-LO o. others

## G. RECESS:

- a. pozi-druve d. phillips e. one way f. saw slotted h. others  
b. 6 - lobes ( Torx from T-10 to T-40 ... ) g. struck slot  
c. combinations ( pozi w/slot, square w/slot, phillips w/slot ... )

## H. FINISH:

- a. plain d. phosphated g. brass j. black-finish  
b. zinc e. chrome h. bronze k. black-oxidized  
c. yellow-zinc f. nickel i. antique-brass l. black-zinc  
m. hot-dip galvanized zinc o. dacrotized 320 q. kylan coating  
n. machanical galvanized p. ruspert r. coating long  
s. special thickness treatment t. wax coated u. others

## I. HEAT-TREATMENT:

- a. hardened b. unhardened c. bright hardened

## J. HEAD PAINTED:

- a. powder & colour b. liquid & colour c. others

## K. PLASTIC COVER:

- a. truss type ( brown ) for outside dia.: 1) 2.40 mm 2) 2.90 mm.  
b. cover type ( white ) for outside dia.: 1) 3.80 mm 2) 4.00 mm.

A	B	C	—	D	E	F	—	G	H	I	—	J	K	L
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

TENGSCREW CO., LTD.  
MR. JOHNSON TENG  
MARKETING MANAGER

OUT

NOV 03 1999

SHORT FORM

\*\*\*\*\*

ROOFING-SCREWS & EPDM-WASHERS

Please indicate the following letters specification , we will supply and offer to our best service to meet your kind rapid inquires.

A. MATERIAL:

- a. carbon steel: C-1022 low carbon steel
b. stainless steel ( AISI series ): a. 410 b. 302HQ c. 305J1

B. THREAD:

- a. self-tapping thread
b. machine thread

- C. STANDARD DIAMETER: # 6 ( 3.5 mm ), # 8 ( 4.2 mm ), #10 ( 4.8 mm ), #12 ( 5.5 mm ), #14 ( 1/4 " = 6.3 mm )

D. THREAD FORMING:

- a. forged-point & number : 1) regular 2) #4 3) #5 4) others
b. milled-point & number : 1) regular 2) others

E. FINISH:

- a. zinc c. ruspert coating e. coating-long g. grey phosphated
b. yellow-zinc d. dacronized 320 f. kylan coating h. black phosphated
i. surface cleaning + passivated

F. FACING:

- a. EPDM : 1. GREY & BLACK ( BONDED EPDM WASHER ) - REGULAR :
a) 14 mm b) 16 mm c) 19 mm d) 22 mm e) 25 mm
2. BLACK ( ONLY SINGLE EPDM ) - WOOD SCREWS :
a) 13 mm b) 18 mm c) 23 mm
3. SPECIAL " BAZ " 25 mm BLACK EPDM ONLY.

b. NEOPRENE

c. SILICON

- d. PVC : 1. GREY & BLACK ( SINGLE " PVC " COMBINED WITH BACKING ):
a) 4.2 mm (# 8) b) 4.8 mm (#10) c) 5.5 mm (#12) d) 6.3 mm (#14)
2. BLACK ( SINGLE " PVC " COMBINED WITH BACKING ):
a) 15 mm b) 18 mm c) 23 mm

G. BACKING:

- a. galvanized steel
b. stainless steel A2 ( AISI 304 stainless steel )
c. aluminum
d. copper

H. BONDED EPDM OR NEOPRENE, SILICON WASHER ( H = G + F ) :

- a1. A) 1) Fa1 + Ga 2) Fa1 + Gb 3) Fa1 + Gc
B) 1) Fa2 + Gb 2) Fa2 + Gd
C) 1) Fa3 + Ga 2) Fa3 + Gb ( ONLY 19 MM BACKING )
b1. 1) Fb + Ga 2) Fb + Gb 3) Fb + Gc 4) Fb + Gd
c1. 1) Fc + Ga 2) Fc + Gb 3) Fc + Gc 4) Fc + Gd
d1. A) 1) Fd1 + Ga 2) Fd1 + Gb 3) Fd1 + Gc 4) Fd1 + Gd
B) 1) Fd2 + Ga 2) Fd2 + Gb 3) Fd2 + Gc 4) Fd2 + Gd

I. FACING IS SUITABLE TO BACKING FOR ITS MAJOR DIAMETER OUTSIDE :

- a. EPDM (regular) 1) 14 mm 2) 16 mm 3) 19 mm 4) 22 mm 5) 25 mm
b. EPDM (woodscrew) 1) 15 mm 2) 20 mm 3) 25 mm
d. PVC (regular) 1) 16 mm 2) 19 mm 3) 23 mm

Grid of boxes for letters A through I, with some boxes empty.

TENGSCREW CO., LTD.
MR. JOHNSON TENG
MARKETING MANAGER

OUT

NOV 03 1999

# SHORT FORM

\*\*\*\*\*

## D. I. N. SPECIFICATION

\*\*\*\*\*

Item No.	Illustration	Standard number
1		DIN 963 DIN 965
2		DIN 84
3		DIN 85
4		DIN 964 DIN 966

Item No.	Illustration	Standard number
60		DIN 7971
61		DIN 7972 DIN 7982
62		DIN 7973 DIN 7983
63		DIN 7981
64		DIN 7976

Item No.	Illustration	Standard number
65		DIN 7985

**TENGSCREW CO., LTD.**

*[Handwritten Signature]*

.....  
**Authorized Signature**

# SHORT FORM

\*\*\*\*\*

## D. I. N. SPECIFICATION

\*\*\*\*\*

Type	Figure	Remaining dimensions in accordance with	Example of designation
K	<p>Head with or without recess, at manufacturer's discretion</p>	Table 3	Drilling screw DIN 7504 - ST 4,2 X 13 - K

Type	Figure	Remaining dimensions in accordance with	Example of designation
L	<p>Remaining dimensions as for type K See table 3 for f and r</p>	Table 3	Drilling screw DIN 7504 - ST 4,2 X 13 - L
N	<p>Cross recessed head (Phillips head) H or Z in accordance with DIN 7962 *)</p>	DIN 7981 *)	Drilling screw DIN 7504 - ST 4,2 X 13 - N - H
P	<p>Cross recessed head (Phillips head) H or Z in accordance with DIN 7962 *)</p>	DIN 7982 *)	Drilling screw DIN 7504 - ST 4,2 X 13 - P - H
Q	<p>Cross recessed head (Phillips head) H or Z in accordance with DIN 7962 *)</p>	DIN 7983 *)	Drilling screw DIN 7504 - ST 4,2 X 13 - Q - H

Item No.	Illustration	Standard number
1		DIN 95 DIN 7995
2		DIN 96 DIN 7996
3		DIN 97 DIN 7997

12	<p>js 16 up to 10 mm; above, js 17</p>	DIN 571
----	--	---------

**TENGSCREW CO., LTD.**

.....  
Authorized Signature